

Traxx (TX) Series

advantage: durability | use: laboratory, clean room, static control/ESD, healthcare, industrial, education

Highlighted by an 18-gauge steel seat, stools in this series are designed to handle tough industrial settings yet can be configured for use in clean rooms.



Dedicated to Design.
Committed to Quality.



- 23" diameter tubular steel (S style) base with 21" diameter affixed footing.



- 25.6" diameter, high-profile cast aluminum (A style) base.



- 25.6" diameter, high-profile reinforced composite (R style) base.



- 28.7" diameter, high-profile wide aluminum (W style) base.



ordering information | august 2018

Traxx Series | Standard Components
 13" dia., 18-gauge steel, soft touch pneumatic seat height adjustment

Models with tubular steel base

Model#	Seat-Hgt.	Compatibility
TXS-L-RC	Low, 15"-19"	Desk
TXS-M-RC	Medium, 18"-25"	Standard Bench
TXS-H-RC	High, 22"-29"	High Bench

Models with cast aluminum base

Model#	Seat-Hgt.	Compatibility
TXA-L-RC	Low, 14"-19"	Desk
TXA-M-RC	Medium, 16"-23"	Standard Bench
TXA-H-RC	High, 19"-29"	High Bench

Models with reinforced composite base

Model#	Seat-Hgt.	Compatibility
TXR-L-RC	Low, 14"-19"	Desk
TXR-M-RC	Medium, 16"-23"	Standard Bench
TXR-H-RC	High, 19"-29"	High Bench

Models with wide aluminum base

Model#	Seat-Hgt.	Compatibility
TXW-L-RC	Low, 14"-19"	Desk
TXW-M-RC	Medium, 16"-23"	Standard Bench
TXW-H-RC	High, 19"-29"	High Bench

Ask about special and custom orders.

optional components

Component	MFG Code	Description
Footring	AFP	Adjustable height, 22" diameter, oval tube construction on solid polished cast aluminum spoke (recommended for medium and high height models with A, W or R bases, adjusts easily without knobs or levers; not available with low height models or units with S style base)
	ATF	Adjustable height, 20" diameter, cast aluminum (recommended for medium and high height models with A, W or R bases. Not available with low height models or S style base units)
Glides	HG	2" high polyamide glides
Casters	RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models
	RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (standard with ESD performance packages)
Miscellaneous	SW	Skid wrapping; net cost per pallet

Category	Class	Current MFG Code	Prior MFG Code
ESD	—*	K	K
Clean Room	ISO 6*	ISO6	1000
	ISO 6 w/S base	ISO6	1000
	ISO 5*	ISO5	VUV
	ISO 5 w/S base	ISO5	VUV
	ISO 4*	ISO4	CR10
	ISO 4 w/S base	ISO4	CR10
Clean Room/ESD	ISO 6/ESD*	ISO6K	1000-K
	ISO 6/ESD w/S base	ISO6K	1000-K
	ISO 5/ESD*	ISO5K	VUV-K
	ISO 5/ESD w/S base	ISO5K	VUV-K
	ISO 4/ESD*	ISO4K	CR10-K
	ISO 4/ESD w/S base	ISO4K	CR10-K
Chrome-plated metal parts, chairs w/A, W, R base	—	C	C
Chrome-plated metal parts, chairs w/S base	—	C	C

*Not available with R style base.

WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

